# DEALER HOT WATER PRESSURE WASHERS **Skid Gasoline/Diesel**

**Belt Drive | HDS Series** 

The HDS Series is the machine professionals go to for the heaviest cleaning applications. This deluxe hot water pressure washer features a heavy-duty wrap around frame with stainless-steel panels for maximum durability.





HDS-3505-0V6G

A Division of Kepner Equipment

### Pump

म

- Belt drive triplex General pump with ceramic plungers - Adjustable high pressure detergent injector

#### Engine

- Performance-proven OHV engine with low-oil protection or liquid-cooled Kubota diesel engine with electric start battery not included

#### Frame

- Heavy-duty powder coated steel square tube skid frame - Stainless-steel coil wrap, control panel and removable front panel

#### Components

- Horizontal schedule 80 pipe coil
- 120V/15-amp auxiliary GFCI outlet
- 2900-watt generator for efficient power to the burner and controls
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- Three-way ball valve for inlet selection
- Detergent and steam valves
- Adjustable thermostat
- Hour meter

#### Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

#### Unit Includes

- Quick connect nozzles 0°, 15°, 25°, 40°, plus wet steam and fixed detergent nozzle
- 50-foot x <sup>3</sup>/<sub>8</sub>-inch steel wire-braided high pressure hose (1/2-inch on HDS-3008 models)
- Adjustable pressure insulated dual lance with fixed detergent nozzle
- Professional-grade insulated trigger gun with safety lock-off

Exclusive Made in Dealer Product CSA

# DEALER HOT WATER PRESSURE WASHERS Skid Gasoline/Diesel

**CHAFFEE-WARD CORPORATION** 



## **Belt Drive | HDS Series**

Gasoline Models										
Model Number	PSI	GPM	Displacement/Engine	Engine Fuel Tank Capacity	Burner Fuel Tank Capacity	Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HDS-3005-0V6G	3000	4.8	480cc Vanguard OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.
HDS-3008-1H6G	3000	7.8	GX690 Honda OHV	10.0 gallons	10.0 gallons	3.67 gph	513,800	50x34x46in.	934 lb.	830 lb.
HDS-3008-0K6G	3000	7.8	725cc Kohler CH730 OHV	10.0 gallons	10.0 gallons	3.67 gph	513,800	50x34x46in.	934 lb.	854 lb.
HDS-3505-1H6G	3500	4.7	GX630 Honda OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.
HDS-3505-0K6G	3500	4.7	624cc Kohler CH620 OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.
HDS-3505-0V6G	3500	4.7	627cc Vanguard OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.
HDS-3506-1H6G	3500	5.6	GX630 Honda OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.
HDS-3506-0K6G	3500	5.6	725cc Kohler CH730 OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.
HDS-4005-2H6G	4000	5.0	GX630 Honda OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.

#### **Diesel Models**

Model Number	PSI	GPM	Horsepower/Engine	Engine Fuel Tank Capacity	Burner Fuel Tank Capacity	Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HDS-3006-0B7G	3000	5.6	16.8 HP Kubota Z602 OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	56.5x34x46in.	940 lb.	836 lb.
HDS-3008-0B7G	3000	7.8	24.8 HP Kubota D902 OHV	10.0 gallons	10.0 gallons	3.67 gph	513,800	56.5x34x46in.	940 lb.	836 lb.
HDS-4005-0B7G	4000	4.5	16.8 HP Kubota Z602 OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	56.5x34x46in.	940 lb.	836 lb.

Description	Fits Models
300°F steam upgrade - Steam option lowers unit pressure to 350-PSI, 240°F rise above ambient with a maximum temperature of 300°F	HDS-3005-0V6G & HDS-3505 models
300°F steam upgrade - Steam option lowers unit pressure to 350-PSI, 240°F rise above ambient with a maximum temperature of 300°F	HDS-3006-0B7G & HDS-3506 models
Four point lifting capability - Allows unit to be lifted by a crane	All models
Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure	HDS-3006-0B7G & HDS-3506 models
Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas	HDS-3005-0V6G
Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas	HDS-3505 models
Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas	HDS-3506 models
Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas	HDS-3006-0B7G
All stainless-steel frame - Converts powder coated painted frame to stainless-steel material	All gasoline models
Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure	HDS-3008 models
Kohler engine upgrade - Higher performance 725cc Kohler CH730 OHV engine	HDS-3008-0K6G
Clutch drive pump - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, changes GPM to 4.3 when added to the unit	HDS-3005-0V6G
Clutch drive pump - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, changes GPM to 4.2 when added to the unit	HDS-3505 models
Clutch drive pump - Stops the pump from spinning in by-pass and helps extend the life of the pump, standard flow rate	HDS-3005 & HDS-3505 models
Clutch drive pump - Stops the pump from spinning in by-pass and helps extend the life of the pump, standard flow rate	HDS-3506 models
Clutch drive pump - Stops the pump from spinning in by-pass and helps extend the life of the pump, standard flow rate	HDS-3008 & HDS-4005 gasoline models
	<ul> <li>300°F steam upgrade - Steam option lowers unit pressure to 350-PSI, 240°F rise above ambient with a maximum temperature of 300°F</li> <li>300°F steam upgrade - Steam option lowers unit pressure to 350-PSI, 240°F rise above ambient with a maximum temperature of 300°F</li> <li>Four point lifting capability - Allows unit to be lifted by a crane</li> <li>Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure</li> <li>Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas</li> <li>Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas</li> <li>Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas</li> <li>Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas</li> <li>Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas</li> <li>Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas</li> <li>All stainless-steel frame - Converts powder coated painted frame to stainless-steel material</li> <li>Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure</li> <li>Kohler engine upgrade - Higher performance 725cc Kohler CH730 OHV engine</li> <li>Clutch drive pump - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, changes GPM to 4.3 when added to the unit</li> <li>Clutch drive pump - Stops the pump from spinning in bypass and helps extend the life of the pump, changes GPM to 4.2 when added to the unit</li> <li>Clutch drive pump - Stops the pump from spinning in by-pass and helps extend the life of the pump, standard flow rate</li> <li>Clutch drive pump - Stops the pump from spinning in by-pass and helps extend the life of the pump, standard flow rate</li> </ul>

\*HX-0149 requires trapping unloader option HX-0152 or HX-0155.

Accessories:					
Part Number	Description	Fits Models			
21-0313	Stainless-steel rain cap - Protects boiler from moisture build-up when unit is left outside	All models			
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models			
850-0324	Gasket (For 50-0170) - Seals between 50-0170 stack adapter and boiler housing	All models			
AW-5740-0000	Wheel kit - Allows unit to become portable	All models			
AW-6000-1006	Hot water skid equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, Mi-T-M logo	All models			
AW-6000-1007	Hot water skid equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, no logo	All models			

### POWERED by HONDA