

DEALER HOT WATER PRESSURE WASHERS

Portable Electric Belt Drive | HHS Series

The best way to tackle the toughest cleaning job is with the HHS Series of pressure washers. Completely portable, easy to use and one of the most reliable in the industry.

CHAFFEE-WARD CORPORATION



A Division of Kepner Equipment



Pump

- Belt drive triplex piston AR or General pump
- Adjustable high pressure detergent injector

Motor

- Open drip-proof electric motor with thermal overload protection
- 35-foot power cord

Frame

- Wrinkle-finish powder coated steel frame assembly
- 13-inch flat-free tires with rear tire brake

Components

- Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Auto start/stop
- Time delay shutdown
- Hour meter
- 10-gallon polyethylene fuel tank
- Racor fuel filter/water separator
- Wand holder
- Adjustable thermostat
- Polyethylene float tank with inlet filter screen

Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F



HHS-2004-2E2G

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25°, 40° and low pressure nozzle
- 50-foot x 3/8-inch high pressure hose with quick connects
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off



All models except
HHS-3005-2E2G
HHS-3005-2E8G

DEALER HOT WATER PRESSURE WASHERS

Portable Electric Belt Drive | HHS Series

CHAFFEE-WARD CORPORATION



A Division of Kepner Equipment

Model Number	PSI	GPM	Horsepower/Motor	Pump	Plug Type	Burner Fuel Tank Capacity	Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHS-1003-2E1G	1000	2.8	2.0 HP, 115V, 1Ø, 20.0A	General	NEMA 5-20P	10.0 gallons	1.84 gph	257,600	57x30x41.5in.	610 lb.	490 lb.
HHS-2004-2E2A	2000	4.2	6.0 HP, 230V, 1Ø, 28.0A	AR	NEMA 6-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E2G	2000	4.2	6.0 HP, 230V, 1Ø, 28.0A	General	NEMA 6-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E3G	2000	4.2	6.0 HP, 230V, 3Ø, 18.5A	General	NEMA L15-20P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E4G	2000	4.2	6.0 HP, 460V, 3Ø, 12.0A	General	NEMA L16-20P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E8G	2000	4.2	6.0 HP, 208V, 1Ø, 29.9A	General	NEMA 6-50P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E9G	2000	4.2	6.0 HP, 208V, 3Ø, 21.0A	General	NEMA L15-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-3004-2E2A	3000	3.9	8.0 HP, 230V, 1Ø, 39.5A	AR	NEMA 6-50P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3004-2E2G	3000	3.9	8.0 HP, 230V, 1Ø, 39.5A	General	NEMA 6-50P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3004-2E3G	3000	3.9	8.0 HP, 230V, 3Ø, 22.5A	General	NEMA L15-30P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3004-2E4G	3000	3.9	8.0 HP, 460V, 3Ø, 14.0A	General	NEMA L16-20P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	720 lb.	600 lb.
HHS-3004-2E5G	3000	3.9	8.0 HP, 575V, 3Ø, 12.0A	General	NEMA L17-30P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	720 lb.	600 lb.
HHS-3004-2E8G	3000	3.9	8.0 HP, 208V, 1Ø, 43.0A	General	NEMA 6-50P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3004-2E9G	3000	3.9	8.0 HP, 208V, 3Ø, 25.5A	General	NEMA L15-30P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3005-2E2G	3000	4.8	10.0 HP, 230V, 1Ø, 46.5A	General	NEMA 6-50P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.
HHS-3005-2E3G	3000	4.8	10.0 HP, 230V, 3Ø, 27.5A	General	NEMA L15-30P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.
HHS-3005-2E4G	3000	4.8	10.0 HP, 460V, 3Ø, 16.5A	General	NEMA L16-20P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	724 lb.	604 lb.
HHS-3005-2E5G	3000	4.8	10.0 HP, 575V, 3Ø, 14.0A	General	NEMA L17-30P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	724 lb.	604 lb.
HHS-3005-2E8G	3000	4.8	10.0 HP, 208V, 1Ø, 50.7A	General	NEMA 6-50P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.
HHS-3005-2E9G	3000	4.8	10.0 HP, 208V, 3Ø, 31.5A	General	NEMA L15-50P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.

Options:

Part Number	Description	Fits Models
HX-0162	Stainless-steel bottom wrap - Converts powder coated painted bottom wrap to stainless-steel	All models
HX-0171	Skid feet - Stationary applications	All models
HX-0172	250°F steam - Increases outlet temperature to 250°F	HHS-3004 models
HX-0174	250°F steam - Increases outlet temperature to 250°F	1000 & 2000-PSI models
HX-0176	250°F steam - Increases outlet temperature to 250°F	HHS-3005 models
HX-0196	Skid frame/roll cage design - Stationary applications	All models
HX-0248	Wireless remote - EZ-quip install	All models
HX-0254	K7 unloader, flow activated (Auto start/stop N/A) - Converts pressure trapping unloader system to flow actuated K7 unloader	HHS-2004 & HHS-3004 models
HX-0255	K7 unloader, flow activated (Auto start/stop N/A) - Converts pressure trapping unloader system to flow actuated K7 unloader	HHS-3005 models

Accessories:

Part Number	Description	Fits Models
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing	All models



NEMA 5-20P,
20-amp plug



NEMA 6-30P,
30-amp plug



NEMA 6-50P,
50-amp plug



NEMA L15-30P,
30-amp plug



NEMA L15-20P,
20-amp plug



NEMA L15-50P,
50-amp plug



NEMA L16-20P,
20-amp plug



NEMA L17-30P,
30-amp plug